

Hardware V1.05

	PTS 230-10	PTS 230-25
System voltage	230VAC	
Input voltage range	200-250VAC	
Frequency	50/60Hz	
Number of inputs	2 (M16 cable glands)	2 (M20 cable glands)
Number of outputs	1 (M16 cable gland)	1 (M16 cable gland)
Max load on output	10Amp. / 2300Watt	25Amp. / 5750Watt
Transfer speed inverter - mains	10 m/s	50 m/s
Transfer speed mains - inverter	500 m/s	20 m/s
Transfer speed mains - inverter by X-com	n.a.	3 ~ 4 sec.
Internal fuse	Glass fuse 8AT	n.a.
Switching possibility for PurePower inverter (X-com)	n.a.	Yes
Potential free contact	n.a.	Yes
Possibility for starting a generator	n.a.	Yes
Possibility for generating a signal	n.a.	Yes
Power consumption (no load)	2 Watt	3 Watt
Input connections	Screw connections 2,5mmq	Screw connections 4mmq
Output connection	Screw connections 2,5mmq	Screw connections 4mmq
Ambiance temperature	-20°C ~ 50°C	
Housing	Polycarbonate	
Protection degree	IP 54	IP 55
Weight (kg)	0,2	0,5
Dimensions (mm)	120x122x56	